


# TECHNICAL DATA SHEET

# HEX HEAD SCREW WITH WASHER

#### PRODUCT DESCRIPTION

A %" (6mm) coarse thread #10 (5 mm) Hex Head Screw with Steel Flat Washer available in three standard lengths; 2" (51 mm), 2 %" (64 mm), and 3" (76 mm). These screws are zinc plated and come with a floating steel flat washer to prevent the screw head from piercing through the material it's being fastened to. Two %" (6 mm) nut drivers are included in each pail of hex head screws.



## **BASIC USES**

The Hex Head Screw is used for multiple applications on the job site. These include securing the alignment system to the forms, for use with the Nudura One Series, and attachment of strapping or buck material to the wall.

# **AVAILABILITY**

The Hex Head Screws are available from your local Nudura distributor. For Distributor locations, visit https://www.nudura.com/.

# **LIMITATIONS**

The Nudura Hex Head Screws are not suitable for permanent installation in an exterior application.

## **PACKAGING**

The Hex Head Screws are packaged 1,000 pieces in a durable clear plastic pail.

- Box Length: 9" (229 mm)Box Width: 9" (229 mm)
- Box Height: Varies 5" (127 mm) to 8" (203 mm)
- Box Weight: Varies 14 lbs (6 kg) to 18 lbs (8 kg)

## **STORAGE**

Store the Hex Head Screws in their original, undamaged packaging within a clean and dry storage area.

Please refer to our website at www.nudura.com for the most up-to-date Product Data Sheets.

NOTE: All Nudura Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

HHSWW-DS/0225

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Probuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



