
PRODUCT DESCRIPTION

The Rebar Bender Cutter is manufactured from durable steel and features shear-cut blades. It is 52" (1.32 m) long and is designed to be mounted on most flat surfaces to enhance leverage and increase safety. The Rebar Bender Cutter is ideal for cutting and bending reinforcing steel to 90° or 180° to be utilized in the Nudura ICF wall system.



FEATURES & BENEFITS

The Rebar Cutter includes two cutting heads capable of cutting up to #5 (15M) reinforcing steel. The rollers used for bending can handle up to a #5 (15M) bar and can bend steel to 90° or 180°.

AVAILABILITY

The Rebar Bender Cutter is available from your local Nudura distributor. For Distributor locations, visit <https://www.nudura.com/>.

STORAGE

Store the Rebar Bender Cutter in their original, undamaged packaging in a clean, dry location.

WARNING

Proper personal protection equipment (PPE) should always be used while working with the Nudura Rebar Bender Cutter to protect from flying debris.

Please refer to our website at www.nudura.com for the most up-to-date Product Data Sheets.

NOTE: All Nudura Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



nudura.com | 866.468.6299



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com