

TECHNICAL DATA SHEET

SURFACE MOUNT BRICK TIE AND PINTLE

PRODUCT DESCRIPTION

The Surface Mount Brick Tie and Pintle is a versatile component designed for use with Nudura Insulated Concrete Form (ICF) systems. The purpose of this product is to securely fasten masonry to the Nudura form. The Brick Tie is fastened using two Nudura Hex Head Screws anywhere along the Nudura fastening strip, while the Pintle connects and supports the masonry.



BASIC USES

The Surface Mount Brick Tie and Pintle is designed to secure masonry to Nudura ICF system. It is suitable for use in various construction applications requiring reliable masonry anchor solutions.

FEATURES & BENEFITS

- This tie is compatible with Nudura pintles as well as other pintles of smaller dimensions, providing flexibility and reliability in various construction scenarios.
- Tested to meet ASTM D754 (USA) and CSA-A370 (CAN) standards for masonry anchors.
- Manufactured with stops that penetrate the foam and prevent the tie from compressing the foam.

AVAILABILITY

The Surface Mount Brick Tie and Pintle is available from your local Nudura distributor. For Distributor locations, visit https://www.nudura.com/.

PACKAGING

The Surface Mount Brick Tie ships in one box of 100 pieces. Pintles are available separately in one box of 100 pieces.

STORAGE

Store the Surface Mount Brick Tie and Pintle in their original, undamaged packaging in a clean, dry location.

Please refer to our website at www.nudura.com for the most up-to-date Product Data Sheets.

NOTE: All Nudura Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

SMBTP-DS/0225

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Probuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



