WEATHER-RESISTANT BARRIER WITH NUDURA ICF

An additional layer of protection

The Enviro-Dri[®] Weather-Resistant Barrier (WRB) System delivers superior air infiltration performance, as measured in air changes per hour, versus house wraps. Applying the Enviro-Dri WRB System on top of Nudura Insulated Concrete Forms (ICF), although not always required, gives the homeowner a piece of mind by providing an additional layer of protection in the face of volatile weather conditions.



Enviro-Dri Field Membrane

When applied on top of the ICF the Enviro-Dri Field Membrane adds an additonal layer of protection on the wall from liquid moisture such as rain, sleet and snow.

Features & Benefits

- No need for mechanical fasteners
- Continuous layer of protections without interruption
- Not affected by the surfacants that can diminish the performance of wraps
- Permanently attached from the moment of application
- Can be sprayed or roller applied on to the ICF







ACCESSORIES

The following two accessory product options can be used on the vertical and horizontal seams of the Nudura ICF prior to Enviro-Dri Field Membrane application. Note these products are meant to be used independent of each other.

Option 1 - Dymonic[®] 100

Dymonic[®] 100 is a high-performance, high-movement, singlecomponent, medium-modulus, low-VOC, UV-stable, non-sag polyurethane sealant.

Features & Benefits:

- Primerless adhesion
- Single-lift application without mesh, laps or seams
- Fast, UV stable cure
- Highly compatible with Enviro-Dri and insulated concrete forms



Option 2 - Enviro-Dri Joint Fabric

The horizontal and vertical joints of the Nudura ICFs can easily be sealed by using Enviro-Dri Joint Fabric and then fully coated and saturated with the Enviro-Dri Field Membrane.

Features & Benefits:

- Ease of use
- Seamless application



Nudura Inc. | 27 Hooper Road, Unit 10 | Barrie, ON L4N 9S3 | 866.468.6299 | nudura.com

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.

Enviro-Dri[®], Dymonic[®] and Tremco[®] are registered trademarks of Tremco CPG Inc. Nudura[®] is a registered trademark of Nudura Inc. Use of the [®] symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office. © Nudura Inc. 2022 ENVIDIN/0722



tremcocpg.com